

Cat5e UTP Patch Cables

Ideal for 1000Base-T Copper Cabling Solution



Overview

Cat5e network patch cable is the cost-effective solution for data center applications. Design for computers, hubs, switches, routers, DSL/cable modems and patch panels in Gigabit datacenter applications. With fast transmission and excellent signal quality, it ensures peak performance through your LAN.

Application

- Rated for any 1000Base-T Ethernet.
- Perfect for data center and SMB applications.
- Ideal for switches, servers, patch panels, or other equipment.

Key Features

- Protected by CM-rated PVC jacket
- Stranded Pure Bare Copper
- RJ45 Plugs with 50 Microinches Gold-plated Connectors
- Snagless Design Protects Clips When Plugging and Unplugging
- Multiple Colors and Lengths Helps Simplify Complicated Cable Runs
- 4 Twisted Pairs and Cross Separator Reduce Crosstalk, Noise and Interference
- Tested with a Fluke DSX-8000 Versiv CableAnalyzer
- CE, Reach, RoHS Certified

Specification

Product Type	
Shielding Type	Unshielded (U/UTP)
Termination End	RJ45 Plug
Reference Standard	ISO/IEC 11801, ANSI/TIA-568.2-D
Conductor	
Conductor Type	Stranded
Conductor Material	Pure Bare Copper
Wire Gauge (AWG)	24 (7/0.20mm)
Conductor Qty.	4 Twisted Pairs
Insulation	
Insulation Material	HDPE
Insulation Diameter (mm)	0.97 ± 0.05
Core Color	A. Orange, White-Orange, B. Blue, White-Blue, C. Green, White-Green, D. Brown, White-Brown
Sheath	
Material	PVC (Complies RoHS), CM
Thickness (mm)	0.55 ± 0.05
Outer O.D. (mm)	5.5 ± 0.4
Color	Blue/Black/Gray/Red/ Green/Yellow/White/Purple
Surface	Clean, Frap, Satiation

Specification

Electrical Characteristics (20 °C)

Data Rate Support	1000Base-T
Standard Bandwidth (MHz)	100
Reference Bandwidth (MHz)	350
1-100MHz, Characteristic Impedance (Ω)	100 ± 15
1-100MHz, Delay Skew (ns/100m)	≤ 45
Max. DC Resistance 20°C ($\Omega/100m$)	9.5

Mechanical Characteristics

Before Aging Tensile Strength (Mpa)	≥ 13.5
Before Aging Elongation (%)	≥ 150
Aging Period (°C×hrs)	100°C×24h×7d
After Aging Tensile Strength (Mpa)	≥ 12.5
After Aging Elongation (%)	≥ 125
Cold Bend (-20±2°C×4h)	No Visible Cracks
Min. Bend Radius (cm)	3.85 ± 0.3

Surface Printing

Letter Height (mm)	3.0 ± 0.3
Color	Black

Others

Rip Cord	Yes
Drain Wire	No