

A solid red circle graphic located to the left of the title text.

# FS S3910 Series Switches Data Sheet

# Contents

|                               |    |
|-------------------------------|----|
| Product overview              | 3  |
| Product highlights            | 4  |
| Platform details              | 4  |
| Platform benefits             | 10 |
| Software requirements         | 11 |
| Product specifications        | 11 |
| Quality certification         | 13 |
| Optics supported              | 13 |
| Warranty, service and support | 13 |
| Ordering information          | 14 |
| Additional information        | 14 |
| Document history              | 14 |

## **Product overview**

S3910 series switches are next-generation gigabit Ethernet switches. They support full gigabit downlink data exchange and fixed 1G/10G uplink data exchange. With the brand-new hardware architecture and FSOS, the S3910 series switches are capable of providing more resource entries, faster hardware processing, and better operation effects, thereby giving you a new experience. The switches also support a wide range of routing protocols, including static routing, Routing Information Protocol (RIP), and Open Shortest Path First (OSPF), which can fully meet requirements for convergence devices on networks of different scales.

The S3910-24TS gigabit Layer 2+ stackable managed switch features 24x 10/100/1000BASE-T and 4x 10Gb SFP+ uplinks that is best for complex environment deployment, which resists corrosion, dust and moisture, supports 0° C ~ 50° C operation and 6KV lightning protection. The 24-port gigabit managed switch equipped with 1+1 hot-swappable dual power supplies, supports 4 units physical stacking to deliver redundancy, simple management and resilience of network capacity. Further, with Broadcom BCM56150 switch chip, S3910-24TS can provide 128 Gbps switching capacity and 96 Mpps forwarding rate to deliver higher network performance. Besides, supporting IPv4/IPv6 and rich layer 3 routing features (static routing, OSPF, RIP, RIPng and etc.), the gigabit switch enables flexible deployment for diverse networking demands.

The S3910-24TF gigabit Layer 2+ stackable managed switch features 24x 10/100/1000BASE-T and 4x 1Gb SFP uplinks that is best for complex environment deployment, which resists corrosion, dust and moisture, supports 0° C ~ 50° C operation and 6KV lightning protection. The 24-port gigabit managed switch supports 4 units physical stacking to deliver redundancy, simple management and resilience of network capacity. Further, with Broadcom BCM56152 switch chip, S3910-24TF can provide 56 Gbps switching capacity and 42 Mpps forwarding rate to deliver higher network performance. Besides, supporting IPv4/IPv6 and rich layer 3 routing features (static routing, OSPF, RIP, RIPng and etc.), the gigabit switch enables flexible deployment for diverse networking demands.

The S3910-48TS gigabit Layer 2+ stackable managed switch features 48x 10/100/1000BASE-T and 4x 10Gb SFP+ uplinks that is best for complex environment deployment, which resists corrosion, dust and moisture, supports 0° C ~ 50° C operation and 6 KV lightning protection. The 48-port gigabit managed switch equipped with 1+1 hot-swappable dual power supplies supports 4 units physical stacking to deliver redundancy, simple management and resilience of network capacity. Further, with Broadcom BCM56150 switch chip, S3910-48TS can provide 176 Gbps switching capacity and 132 Mpps forwarding rate to deliver higher network performance. Besides, supporting IPv4/IPv6 and rich layer 3 routing features (static routing, OSPF, RIP, RIPng and etc.), the gigabit switch enables flexible deployment for diverse networking demands.

The S3910-48TF gigabit Layer 2+ stackable managed switch features 48x 10/100/1000BASE-T and 4x 1Gb SFP uplinks that is best for complex environment deployment. The 48-port gigabit managed switch supports 4 units physical stacking to deliver redundancy, simple management and resilience of network capacity. Further, with Broadcom BCM56152 switch chip, S3910-48TF can provide 104 Gbps switching capacity and 78 Mpps forwarding rate to deliver higher network performance. Besides, supporting IPv4/IPv6 and rich layer 3 routing features (static routing, OSPF, RIP, RIPng and etc.), the gigabit switch enables flexible deployment for diverse networking demands.

## Product highlights

- Broadcom Chip, Support 4 Units Stacking
- 1+1 Hot-swappable Power Supplies (Only for S3910-24TS and S3910-48TS Switch)
- Support Layer 3 Features (RIP, OSPF, VRRP, etc.)
- Support WEB/CLI/SNMP/SSH for Flexible Operation
- Network Monitoring through Sampled Flow (sFlow) (Only for S3910-24TS and S3910-48TS Switch)
- Support SSH, ACL, AAA, 802.1X, RADIUS, TACACS+, etc. for Security
- ≥6KV Lightning Protection (Only for S3910-24TS, S3910-24 TF and S3910-48TS Switch)

## Platform details

### Switch models and configurations

Figures 1 through 4 show the FS S3910 series switches.




**Figure 1.**

S3910-24TS, 24-Port Gigabit Ethernet L2+ Switch, 24 x Gigabit RJ45, with 4 x 10Gb SFP+ Uplinks, Stackable Switch, Broadcom Chip




**Figure 2.**

S3910-24TF, 24-Port Gigabit Ethernet L2+ Switch, 24 x Gigabit RJ45, with 4 x 1Gb SFP Uplinks, Stackable Switch, Broadcom Chip, Fanless

## Platform details

### Switch models and configurations




**Figure 3.**

S3910-48TS, 48-Port Gigabit Ethernet L2+ Switch, 48 x Gigabit RJ45, with 4 x 10Gb SFP+ Uplinks, Stackable Switch, Broadcom Chip




**Figure 4.**

S3910-48TF, 48-Port Ethernet L2+ Switch, 48 x Gigabit RJ45, with 4 x 1Gb SFP Uplinks, Stackable Switch, Broadcom Chip

## Switch configurations and port density

Table 1 shows the FS S3910 series configurations and port density.

**Table 1. Switch configuration and port density**

| FS P/N                               | S3910-24TS                                                                                                                      | S3910-24TF                                                                                                                             | S3910-48TS                                                                                                                      | S3910-48TF                                                                                          |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Description                          | S3910-24TS, 24-Port Gigabit Ethernet L2+ Switch, 24 x Gigabit RJ45, with 4 x 10Gb SFP+ Uplinks, Stackable Switch, Broadcom Chip | S3910-24TF, 24-Port Gigabit Ethernet L2+ Switch, 24 x Gigabit RJ45, with 4 x 1Gb SFP Uplinks, Stackable Switch, Broadcom Chip, Fanless | S3910-48TS, 48-Port Gigabit Ethernet L2+ Switch, 48 x Gigabit RJ45, with 4 x 10Gb SFP+ Uplinks, Stackable Switch, Broadcom Chip | S3910-48TF, 48-Port Ethernet L2+ Switch, 48 x Gigabit RJ45, with 4 x 1Gb SFP Uplinks, Broadcom Chip |
| <b>Port</b>                          |                                                                                                                                 |                                                                                                                                        |                                                                                                                                 |                                                                                                     |
| 1G port density                      | 24                                                                                                                              | 28                                                                                                                                     | 48                                                                                                                              | 52                                                                                                  |
| 10G port density                     | 4                                                                                                                               | -                                                                                                                                      | 4                                                                                                                               | -                                                                                                   |
| 25G port density                     | -                                                                                                                               | -                                                                                                                                      | -                                                                                                                               | -                                                                                                   |
| 40G port density                     | -                                                                                                                               | -                                                                                                                                      | -                                                                                                                               | -                                                                                                   |
| 100G port density                    | -                                                                                                                               | -                                                                                                                                      | -                                                                                                                               | -                                                                                                   |
| 10G port density with breakout cable | -                                                                                                                               | -                                                                                                                                      | -                                                                                                                               | -                                                                                                   |
| 25G port density with breakout cable | -                                                                                                                               | -                                                                                                                                      | -                                                                                                                               | -                                                                                                   |
| 40G port density with breakout cable | -                                                                                                                               | -                                                                                                                                      | -                                                                                                                               | -                                                                                                   |
| Management ports                     | -                                                                                                                               | -                                                                                                                                      | -                                                                                                                               | -                                                                                                   |
| Console port                         | 1                                                                                                                               | 1                                                                                                                                      | 1                                                                                                                               | 1                                                                                                   |
| USB port                             | -                                                                                                                               | -                                                                                                                                      | -                                                                                                                               | -                                                                                                   |

## Memory and processor

|              |                               |                       |                              |                               |
|--------------|-------------------------------|-----------------------|------------------------------|-------------------------------|
| Switch chip  | BCM56150                      | BCM56152              | BCM56150                     | BCM56152                      |
| CPU          | ARM A9 Single-Core CPU, 1 GHz | Single-Core CPU, 1GHz | ARM A9 Single-Core CPU, 1GHz | ARM A9 Single-Core CPU, 1 GHz |
| DRAM         | -                             | -                     | -                            | -                             |
| SDRAM        | 512MB                         | 512MB                 | 512MB                        | 512MB                         |
| Flash memory | 256MB                         | 256MB                 | 256MB                        | 256MB                         |

| FS P/N        | S3910-24TS | S3910-24TF | S3910-48TS | S3910-48TF |
|---------------|------------|------------|------------|------------|
| Latency       | 1.955us    | 1.955us    | 1.955us    | 1.955us    |
| Packet buffer | 1.5MB      | 1.5MB      | 1.5MB      | 1.5MB      |

**Note:**

RJ45 ports can be used as 10/100/1000BASE-T ports for Ethernet connection.

SFP ports can be used for 100M/1G connection.

SFP+ports can be used for 1/10G connection.

**Power supplies and fans**

The FS 3910 Series switches ship with the dual 1+1 redundant power supply as default.

Table 2 provides more details on the FS S3910 series power supplies and fan specifications.

**Table 2. Power supply and fan specifications**

| Description                       | S3910-24TS                       | S3910-24TF                                                          | S3910-48TS                       | S3910-48TF                              |
|-----------------------------------|----------------------------------|---------------------------------------------------------------------|----------------------------------|-----------------------------------------|
| Power supply                      | 2 (1+1 Redundancy) Hot-swappable | 1 Built-in                                                          | 2 (1+1 Redundancy) Hot-swappable | 1 Built-in                              |
| Fan number                        | 1x Built-in Fan                  | Fanless                                                             | 1x Built-in Fan                  | 1x Built-in Fan                         |
| Airflow                           | Right-to-Left                    | -                                                                   | Right-to-Left                    | Left-to-Right                           |
| Acoustic noise                    | ≤78dB                            | -                                                                   | ≤78dB                            | ≤47dB                                   |
| Maximum fan speed                 | -                                |                                                                     |                                  |                                         |
| Max. power consumption            | 27W                              | 24W                                                                 | 48W                              | 40W                                     |
| Power max rating                  | 70W                              | 24W                                                                 | 70W                              | 66W                                     |
| Input-voltage range and frequency | 100-240VAC, 50-60Hz, 2A          | 100-240VAC, 50-60Hz, 0.6A                                           | 100-240VAC, 50-60Hz, 2A          | 100VAC~240VAC, 50~60Hz<br>192VDC~288VDC |
| Power supply efficiency           | >85%@100% load                   | ≥80%@100% load (PSL25-12A-RA)<br>≥81% @50%~100% load (PSL25-12A-RA) | >85%@100% load                   | ≥85%@100% load                          |
| Input current                     | 2A                               | 0.6A                                                                | 2A                               | 1.5A                                    |
| Output ratings                    | 11.4V~12.4V                      | 11.64V~12.36V                                                       | 11.4V~12.4V                      | 11.64V~12.36V                           |

| Description                    | S3910-24TS | S3910-24TF | S3910-48TS | S3910-48TF |
|--------------------------------|------------|------------|------------|------------|
| Output holdup time             | ≥60ms      | ≥20ms      | ≥60ms      | ≥20ms      |
| Power-supply input receptacles | C13        | C13        | C13        | C13        |
| Power cord rating              | 10A        | 10A        | 10A        | 10A        |

## Stacking

The FS 3910 Series switch models are designed for stacking switches as a single virtual switch, enabling customers to have a single management plane and control plane for up to 192 access ports.

Table 3 lists the supported stacking options.

**Table 3. Supported stacking options**

| Part Name                   | S3910-24TS                                                         | S3910-24TF                                           | S3910-48TS                                                         | S3910-48TF                                           |
|-----------------------------|--------------------------------------------------------------------|------------------------------------------------------|--------------------------------------------------------------------|------------------------------------------------------|
| Stacking ports              | Port25-28 (4*10G)                                                  | Port25-28 (4*1G)                                     | Port51-52 (2*10G)                                                  | Port51-52 (2*1G)                                     |
| Supported stack members     | Stack with S3910-48TS or other S3910-24TS with the same OS version | Stack with other S3910-24TF with the same OS version | Stack with S3910-24TS or other S3910-48TS with the same OS version | Stack with other S3910-48TF with the same OS version |
| Maximum number of VSL links | 4                                                                  | 4                                                    | 2                                                                  | 2                                                    |
| Number of members           | 4                                                                  | 4                                                    | 4                                                                  | 4                                                    |

### Note:

All 10G ports can be stacked by transceivers or DAC/AOC lines, supporting port mixing, each 10G port is a stack group.

## Switch performance

Table 4 shows performance specifications for the FS S3910 series switches.

**Table 4. Performance specifications**

| Performance for all S3910 Series Switches                | S3910-24TS | S3910-24TF | S3910-48TS | S3910-48TF |
|----------------------------------------------------------|------------|------------|------------|------------|
| Switching capacity                                       | 128 Gbps   | 56 Gbps    | 176 Gbps   | 104 Gbps   |
| Forwarding rate                                          | 96 Mpps    | 42 Mpps    | 132 Mpps   | 78 Mpps    |
| Total number of MAC addresses                            | 16K        | 16K        | 16K        | 16K        |
| Total number of IPv4 routes (indirect routes)            | 500        | 500        | 500        | 500        |
| Total number of IPv4 host routes (direct routes and ARP) | 500        | 500        | 500        | 500        |
| Total number of IPv6 routes (indirect routes)            | 500        | 500        | 500        | 500        |
| Total number of IPv6 host routes (direct routes and NDP) | 500        | 500        | 500        | 500        |
| Total number of IPv4 multicast routes                    | -          | -          | -          | -          |
| Total number of IPv6 multicast routes                    | -          | -          | -          | -          |
| QoS ACL scale                                            | 1500       | 1500       | 1500       | 1500       |
| Security ACL scale                                       | 1500       | 1500       | 1500       | 1500       |
| VLAN IDs                                                 | 4000       | 4000       | 4000       | 4000       |
| STP virtual ports (port* VLANs) for MST                  | 64         | 64         | 64         | 64         |
| Total switched virtual interfaces (SVIs)                 | 500        | 500        | 500        | 500        |
| Jumbo frame                                              | 9216 bytes | 9216 bytes | 9216 bytes | 9216 bytes |

## Platform benefits

Table 5 lists the software spotlights for the FS S39110 series switches.

**Table 5. Software spotlights**

| Functionality                                  | Description                                                                                                                                                                                                                                                                                                                     |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| High Availability And Multi-Service Support    | Support stacking links<br>Support line-rate IPv4/IPv6 dual-stack multi-layer switching<br>Support a wide range of IPv4 routing protocols, including static routing, RIP, and OSPF<br>Support 802.1p/DSCP/TOS traffic classification<br>Support the IPv4 and IPv6 multicast functions<br>Support Energy Efficient Ethernet (EEE) |
| Error-Free Network Configuration               | Support Syslog, Web-based management, Telnet, SSH<br>Support ERPS<br>Support IPv4/IPv6/MAC/ARP ACL<br>Support LLDP (802.1ab)<br>Support sFlow<br>Support SNMP V1/V2/V3                                                                                                                                                          |
| Secure And Simplified Access for Users And LoT | Support 3-tuple binding (IP address, MAC address, and port)<br>Support filtering of invalid MAC addresses, Port- and MAC-based 802.1x authentication, MAB authentication<br>Support RADIUS and TACACS+<br>Support AAA (IPv4/IPv6) for device login management<br>Support SSH and SSH V2.0<br>Support ARP spoofing prevention    |

## Software requirements

The FS S3910 Series Switches run on FS OS Software version.

Table 6 lists the latest software requirements for the switch models.

**Table 6. Latest software requirements**

| FS P/N     | Description                                                                                                                            | Latest software requirements                                                  |
|------------|----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| S3910-24TF | S3910-24TF, 24-Port Gigabit Ethernet L2+ Switch, 24 x Gigabit RJ45, with 4 x 1Gb SFP Uplinks, Stackable Switch, Broadcom Chip, Fanless | <a href="#">S3910-24TF Switch FSOS 11.4.1 B74S3 Software</a>                  |
| S3910-24TS | S3910-24TS, 24-Port Gigabit Ethernet L2+ Switch, 24 x Gigabit RJ45, with 4 x 10Gb SFP+ Uplinks, Stackable Switch, Broadcom Chip        | <a href="#">S3910-24TS and S3910-48TS Switches FSOS 11.4.1 B74S3 Software</a> |
| S3910-48TS | S3910-48TS, 48-Port Gigabit Ethernet L2+ Switch, 48 x Gigabit RJ45, with 4 x 10Gb SFP+ Uplinks, Stackable Switch, Broadcom Chip        |                                                                               |
| S3910-48TF | S3910-48TF, 48-Port Ethernet L2+ Switch, 48 x Gigabit RJ45, with 4 x 1Gb SFP Uplinks, Broadcom Chip                                    | /                                                                             |

## Product specifications

Table 7 shows the product specifications for the FS S3910 series switches.

**Table 7. Product specifications**

| Description           | S3910-24TS                  | S3910-24TF                  | S3910-48TS                  | S3910-48TF                  |
|-----------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| <b>Environmental</b>  |                             |                             |                             |                             |
| Operating temperature | 0 to 50°C (32 to 122° F)    | 0 to 50°C (32 to 122°F)     | 0 to 50°C (32 to 122° F)    | 0 to 50°C (32 to 122° F)    |
| Storage temperature   | -40 to 70°C (-40 to 158° F) | -40 to 70°C (-40 to 158°F)  | -40 to 70°C (-40 to 158°F)  | -40 to 70°C (-40 to 158° F) |
| Operating humidity    | 10% to 90% (Non-condensing) | 10% to 90% (Non-condensing) | 10% to 90% (Non-condensing) | 10% to 90% (Non-condensing) |
| Temperature alarm     | Supported                   | Supported                   | Supported                   | Supported                   |
| Acoustic noise        | <60dB                       | None                        | <60dB                       | <47dB                       |

| Description                        | S3910-24TS                                                                                                                                                                                                                                                                                                                                                                                                                                 | S3910-24TF                             | S3910-48TS                               | S3910-48TF                           |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|------------------------------------------|--------------------------------------|
| Physical specifications            |                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                        |                                          |                                      |
| Dimensions (HxWxD)                 | 1.72"x17.32"x9.69" (43.6x 440x 246.1mm)                                                                                                                                                                                                                                                                                                                                                                                                    | 1.75"x17.44"x10.24" (44.5x 443x 260mm) | 1.72"x17.32"x13.68" (43.6 x440x 347.6mm) | 1.75"x17.44"x10.55"(44.5 ×443×268mm) |
| Rack units (RU)                    | 1U                                                                                                                                                                                                                                                                                                                                                                                                                                         | 1U                                     | 1U                                       | 1U                                   |
| Weight                             | 3.97kg                                                                                                                                                                                                                                                                                                                                                                                                                                     | 3.05kg                                 | 5.23kg                                   | 3.67kg                               |
| Electrical                         |                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                        |                                          |                                      |
| Voltage (auto ranging)             | 100-240VAC                                                                                                                                                                                                                                                                                                                                                                                                                                 | 100-240VAC                             | 100-240VAC                               | 100-240VAC                           |
| Frequency                          | 50-60Hz                                                                                                                                                                                                                                                                                                                                                                                                                                    | 50-60Hz                                | 50-60Hz                                  | 50-60Hz                              |
| Current                            | 2A                                                                                                                                                                                                                                                                                                                                                                                                                                         | 0.6A                                   | 2A                                       | 1.5A                                 |
| Power rating (maximum consumption) | 27W                                                                                                                                                                                                                                                                                                                                                                                                                                        | 24W                                    | 48W                                      | 40W                                  |
| Mean-time between failures         |                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                        |                                          |                                      |
| MTBF (hours)                       | >200K                                                                                                                                                                                                                                                                                                                                                                                                                                      | >200K                                  | >200K                                    | >200K                                |
| Connectors                         |                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                        |                                          |                                      |
| Connectors and cabling             | <ul style="list-style-type: none"><li>1GBASE-T ports: RJ-45 connectors, 4-pair Cat5E/Cat6/Cat6a UTP cabling</li><li>SFP transceivers: LC fiber connectors (single-mode or multimode fiber)</li><li>SFP+ transceivers: LC fiber connectors (single-mode or multimode fiber)</li><li>FS StackWise stacking ports: DAC/AOC/copper-based FS StackWise cabling</li><li>Management console port: RJ-45-to-DB9 cable for PC connections</li></ul> |                                        |                                          |                                      |
| Power connectors                   | <ul style="list-style-type: none"><li>Customers can provide power to a switch by using the internal power at the back of the switchInternal power supply connector: The internal power supply is an auto-ranging unit. It supports input voltages between 100 (115 for 1100WAC) and 240 VAC. Use the supplied AC power cord to connect the AC power connector to an AC power outlet</li></ul>                                              |                                        |                                          |                                      |
| Standards                          |                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                        |                                          |                                      |
| Standards                          | -                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                        |                                          |                                      |

## Quality certification

At FS, our Quality Commitment lies in all aspects of processes, resources, and methods that enable us to build superior networks for our customers. Through a quality policy focusing on continuous improvement of products and services, we're able to achieve the highest levels of satisfaction for our customers. To that end, every FS employee is accountable for contributing to the value of the products and services we deliver.

Figures 5/6 shows some of the authoritative certifications obtained by FS S3910 Series Switches.



Figure 5. S3910-24TS/S3910-24TF/ S3910-48TS



Figure 6.S3910-48TF

## Optics supported

For details about the optical modules available, visit:

S3910-24TS/S3910-48TS: [Transceivers DACs and AOCs Supported on S3910-24TS and S3910-48TS Switch](#)

S3910-24TF: [Transceivers DACs and AOCs Supported on S3910-24TF Switch](#)

## Warranty, service and support

FS S3910 Series Switches enjoy 5 years limited warranty against defects in materials or workmanship. For more information for FS Returns & Refunds policy, visit <https://www.fs.com/policies/warranty.html> or [https://www.fs.com/policies/day\\_return\\_policy.html](https://www.fs.com/policies/day_return_policy.html)

FS provides a personal account manager, free professional technical support, and 24/7 live customer service to each customer.[support.html](https://www.fs.com/support.html)

- Professional Lab: Test each product with the latest and advanced networking equipment.
- Free Technical Support: Provide free & tailored solutions and services for your businesses.
- 80% Same-day Shipping: Immediate shipping for in-stock items.
- Fast Response: Direct and immediate assistance from an expert.

For more information, visit [https://www.fs.com/service/fs\\_support.html](https://www.fs.com/service/fs_support.html)

## Ordering information

Table 8 provides the ordering information for S5810 series switches.

**Table 8. Ordering information**

| FS P/N                     | Product description                                                                                                                    |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Switch hardware</b>     |                                                                                                                                        |
| <a href="#">S3910-24TS</a> | S3910-24TS, 24-Port Gigabit Ethernet L2+ Switch, 24 x Gigabit RJ45, with 4 x 10Gb SFP+ Uplinks, Stackable Switch, Broadcom Chip        |
| <a href="#">S3910-24TF</a> | S3910-24TF, 24-Port Gigabit Ethernet L2+ Switch, 24 x Gigabit RJ45, with 4 x 1Gb SFP Uplinks, Stackable Switch, Broadcom Chip, Fanless |
| <a href="#">S3910-48TS</a> | S3910-48TS, 48-Port Gigabit Ethernet L2+ Switch, 48 x Gigabit RJ45, with 4 x 10Gb SFP+ Uplinks, Stackable Switch, Broadcom Chip        |
| <a href="#">S3910-48TF</a> | S3910-48TF, 48-Port Ethernet L2+ Switch, 48 x Gigabit RJ45, with 4 x 1Gb SFP Uplinks, Stackable Switch, Broadcom Chip                  |

## Additional information

For more information about the S3910 Series Switches, contact your account manager or visit

[https://www.fs.com/search\\_result?keyword=S3910](https://www.fs.com/search_result?keyword=S3910)

## Document history

| New or revised topic                           | Described in | Date     |
|------------------------------------------------|--------------|----------|
| Updates to FS S3910 Series Switches Data Sheet | Updated all  | 1/9/2023 |